

OPTILOCK

Protection for sliding doors



FEATURES AND BENEFITS OF THE PRODUCT

- Mechanical and electronic protection for glass sliding doors of up to 8 mm in thickness. The distance between the panes should be minimum 7 mm.
- Quick and easy installation by personnel – without using tools, stickers and drilling.
- Automatic locking of the OptiLock – one does not have to remember to lock it using a remote control.
- Universal USER remote control for controlling all cabinets protected by the OptiLocks.
- Long battery life – up to 2 years of using without the necessity to replace it frequently.
- Symmetrical shape – universal for both left and right doors.

CAUTION!

Before mounting the OptiLock make sure that the USER remote control is programmed with the device!

After being taken out of the box, the OptiLock is in the sleep mode. Pushing the „Press” button wakes up and activates the OptiLock.



The periodically blinking (every 1 second) red LED indicates lack of programmed remote controls.



OPTILOCK

Protection for sliding doors

Aim the USER remote control at the periodically blinking (every 1 second) red LED. Push and hold the left button on the remote control (closed padlock). Hold the button on the remote control until the OptiLock emits a short acoustic signal and the LED starts blinking every 2 seconds.



In order to check whether the USER remote control has been properly programmed push the right button (open padlock), which will open the OptiLock and make pulling the protective slat out possible. Then push the left button (closed padlock), which will close the OptiLock and indicate that the remote control is properly programmed.



In order to program another USER remote control push and hold for 2 seconds the little switch in the groove underneath the OptiLock.



An indication of entering the programming mode is a short acoustic signal and the periodically blinking red LED. Then follow the instructions as above in the points 3, 4 and 5.

